

## Frameless Bezel Installation Guide

## Safety

Aquavision recommends that installation be carried out by a qualified installer. Ensure that the latest local wiring and safety regulations are adhered during installation. Your Aquavision will be powered by a 12 or 24V DC power supply. This must be positioned away from any water source. Observe the correct safety zones within the bathroom/wet zone. The Classic Bezel and optional back box must be earthed. The bezel is to be mounted on a vertical wall only and not on a sloping wall or a ceiling.

IF IN DOUBT REFER TO A QUALIFIED PERSON. THIS APPLIANCE AND THE BEZEL MUST BE EARTHED

## Classic Bezel installation, cable feed & waterproofing

- 1. Once the position of the Aquavision has been defined, make a cut out according to the dimensions in the table below. Ensure the wall is now finished (tiled/painted etc.) Tiles must run right up to the edge of the cut out.
- 2. Fit the 2 mounting brackets supplied to the Bezel using the screws provided.
- 3. Apply a generous bead of clear silicone to the outside edge of the Bezel. This creates a waterproof seal between mounting surface and Bezel. Failure to do this will prevent you Aquavision from being waterproofed. See Fig 2
- Offer the Bezel up to the hole you cut earlier, ensuring to observe 4. the correct orientation (Bezels with arrows face upwards, Bezels without arrows are not orientation dependant)
- 5. Secure the Bezel using screws on the inside edge of the brackets. Once fitted the Bezel should be able to withstand a pull force of 100Kg.
- 6. Wipe away any excess silicone.
- Run all cables supplied and any additional input cables as shown in 7. Fig 1. Ensure there is enough slack on the cables as this will make connecting the TV easier. Do not extend/shorten the power supply cable as this will invalidate you warranty and potentially damage the TV.
- The Bezel is now ready to accommodate the TV and Classic Glass 8. components. The instructions for fitting these items are provided separately.

Fig 1: TV a e ria l input speakercable (not supplied) supplied) Audio & Video inputs (not supplied) integral powe supply cable ١ì Mains lead (supplied)

IMPORTANT: Failure to follow these instructions thoroughly will prevent the Aquavision from being properly waterproofed. TV's installed incorrectly which suffer water damage are not covered under warranty.

Screen Details	22"	27"
Screen Size	21.6"	27"
Overall/Cut-	395 × 560mm	476 × 706mm
Out Size	15 <sup>5</sup> / <sub>8</sub> " × 22 <sup>1</sup> / <sub>8</sub> "	18 <sup>3</sup> / <sub>4</sub> " × 27 <sup>7</sup> / <sub>8</sub> "
Screen	45mm	45mm
Depth	1 <sup>7</sup> /8"	1 <sup>7</sup> / <sub>8</sub> "



Clifton Park, NY 12065 America +1 800 524 1804

www.aquavsion.tv www.aquavision.us

∎∎ë,		<b>HEAD</b> Aquav
e. 8	le.	Unit 2 Horsfi
	12	Chesh
日版	5.5	Unite +44 [

## D OFFICE AND FACTORY vision

2 Grosvenor Business Park field Way, Stockport hire, SK6 2SU ed Kingdom [0]1617111900